CAD generated and maintained drawing. All printed and electronic copies outside of PSG - Dover's engineering database are "Uncontrolled" and shall be used for reference only. DESCRIPTION NOTES: UNLESS OTHERWISE SPECIFIED RELEASED INTO PRODUCTION SEE ECN #GRT000022 1. DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994. 2. * INDICATES DIMENSIONS AND/OR FEATURES MODIFIED ON CURRENT REV LEVEL. 3. MINIMUM DIMENSION FOR REPACKING. THIS DRAWING DOES NOT SHOW DETAILS OF ALL OPTIONS AND ACCESSORIES - 34.00 -10.05 -2X 5" ANSI PORTS 2" NPT--1-1/2" NPT 9.50 - 5.00 -Ø2.44 .62 X .31 KEYWAY 9.50 4X 3/4" NPT-2X 1-1/2" NPT 12.00 4X Ø.75 Ø8.50 5.00 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF PGG - A DOVER COMPANY. TIS RECEIPT AND POSSESSION DO NOT CONVEY ANY RIGHT SO THE PRODUCE ON DESCRIPTION OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE SUBJECT TO RETURN UPON REQUEST. PREPODUCTION, DESCOURSE TO SET WITHOUT THE WRITTEN AUTHORIZATION OF DOVER COMPORTION IS STRICTLY PORRIDGEN. BLACKMER® PUMPS 1809 CENTURY AVE SW GRAND RAPIDS, MI USA 49503 TELEPHONE: 616-241-1611 WWW.BLACKMER.COM DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:

PUMP ASSEMBLY, DIMENSIONAL DECIMALS .XX ± THIRD ANGLE PROJECTION V2-423, JACKETED HEAD, NON-JK PRV ANGLES LM0047

2017-12-22

A REV

1 OF 1