

CRYSTAL CLEAN 140+



Material Safety Data Sheet

Heritage Crystal Clean, L.L.C.
3970 West 10th Street
Indianapolis, Indiana 46222

Company Contact: Steve Johnson
Telephone: 317-486-2770
Fax: 317-486-5087
E-Mail: steve.johnson@crystal-clean.com

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

EMERGENCY TELEPHONE NUMBERS:

CHEMTREC 800-424-9300 (24 hours)
Heritage Group Safety Office 317-875-4670 (Work hours)

Product Name: CRYSTAL CLEAN 140+
CAS Number: Mixture
Chemical Name: Mineral Spirits
Chemical Family: Petroleum aliphatic hydrocarbon
MSDS Number: 467
Synonyms: Mineral Spirits, Naphtha, Parts Washing Solvent, Stoddard Solvent

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient Name	CAS Number	Percent By Weight
Petroleum Hydrocarbon Naphtha	Mixture	100

This solvent material may be produced from several sources utilizing different refining processes that generate different CAS registry numbers based on the refining process used. Petroleum solvent naphtha, medium aliphatic is a complex stream of predominantly C9 to C12 hydrocarbons. The exact composition and concentrations vary.

3. HAZARDS IDENTIFICATION

Eye Hazards:

This material may cause temporary discomfort or irritation to the eyes. Symptoms may include stinging, tearing, redness, and swelling of the eyes.

Skin Hazards:

May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, cracking of the skin, burns, and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion Hazards:

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs (aspiration) during swallowing or vomiting resulting in lung inflammation or other lung injury such as fatal chemical pneumonitis.

CRYSTAL CLEAN 140+

Inhalation Hazards:

Breathing of vapor or mist is possible and may be irritating to the respiratory system. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. In applications where vapors (caused by high temperatures) or mists (caused by mixing) are created, breathing may cause a mild burning sensation in the nose, throat, and lungs. Breathing of high vapor concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea, and loss of coordination. Continued inhalation may result in unconsciousness and death.

Signs and Symptoms:

Signs of central nervous system depression begin with headache, dizziness, apparent intoxication, and progress through loss of consciousness.

Conditions Aggravated by Exposure:

Skin contact can aggravate existing dermatitis. Preexisting eye and respiratory disorders may also be aggravated by exposure to this product.

4. FIRST AID MEASURES

Eyes:

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush with large quantities of water for at least 15 minutes while holding eyelids apart. Seek immediate medical attention.

Skin:

Remove contaminated clothing. Flush exposed area with large amounts of water. Wash skin with soap and water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion:

DO NOT induce vomiting. Contact physician, Poison Control Center, hospital emergency room, or physician immediately for further medical assistance and advice. Have victim rinse mouth with water to remove taste from mouth. If victim is coughing, choking, has shortness of breath, or difficulty in breathing, transport to nearest medical facility for additional treatment. If any of the delayed signs and symptoms appear within the next 6 hours, transport to nearest medical facility: fever greater than 101° F, shortness of breath, chest congestion, or continued coughing or wheezing. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Inhalation:

If user experiences symptoms, move individual away from exposure and into air free of vapors. If symptoms persist, seek medical attention. If victim has difficulty in breathing, tightness of the chest, is dizzy, is vomiting, or is unresponsive, administer oxygen or artificial respiration or CPR if required until medical assistance can be rendered and transport to the nearest medical facility.

5. FIRE FIGHTING MEASURES

Flash Point: >141° F, >60.56° C
Flash Point Method: TCC
Autoignition Point: >440° F, >226° C
Flammability Class: III-A Combustible Liquid (NFPA 30)
Lower Explosive Limit: 1%
Upper Explosive Limit: 6%

CRYSTAL CLEAN 140+

Fire and Explosion Hazards:

Vapors are heavier than air and may travel along the ground or be moved by Ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product, including residue, may ignite explosively.

Extinguishing Media:

Use water fog, carbon dioxide, dry chemical, or regular foam. Do not use a direct stream of water. Material will float and can be reignited on the surface of water.

Fire Fighting Instructions:

Flammable material. Clear fire area of non-emergency personnel. Do not enter confined fire space without full bunker gear including a positive pressure NIOSH-approved self-contained breathing apparatus. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up resulting in container rupture. In advanced fires, maintain safe distance from sealed containers.

6. ACCIDENTAL RELEASE MEASURES

Small spills can be absorbed by appropriate inert absorbent such as vermiculite, floor absorbent, absorbent booms or pads. Avoid breathing vapors. Ventilate the area.

Large Spills: Eliminate all sources of ignition. Persons not wearing protective equipment should be excluded from the area of the spill until clean-up has been completed. Stop spill at source if safe to do so. Prevent material from entering basements, confined areas, drains, sewers, streams, or other bodies of water. Prevent from spreading by diking or other means of containment. If runoff occurs, notify authorities as required that a spill has occurred. Pump or vacuum spilled product into clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil, and other materials to proper non-leaking closed containers for disposal.

7. HANDLING AND STORAGE

Handling and Storage Precautions:

Keep containers closed when not in use. When opening covers and outlet caps on storage tanks, use face shield and gloves to avoid possible injury from pressurized hydrocarbon vapors. Do not overheat. Surfaces that are sufficiently hot may ignite liquid material. All five-gallon pails and larger containers, including tank cars and truck cargo tanks should be grounded and/or bonded when material is transferred to prevent ignition of vapors by static electricity. Hydrocarbon solvents are basically non-conductors of electricity but can become electrostatically charged during mixing, filtering, or pumping at high flow rates. If the charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids.

Store in a cool, dry, well-ventilated safety storage cabinet or room with appropriate labels. Do not store in closed vehicles. Keep away from ignition sources and ground all equipment containing this material. Containers must be able to withstand expansion and/or pressures expected from warming and cooling in storage.

Empty Container Warning: Empty containers contain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Work/Hygienic Practices:

Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after use. Thoroughly clean and launder any clothing or protective equipment which has been contaminated prior to reuse or wearing after handling this product.

CRYSTAL CLEAN 140+

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below the permissible exposure limits and threshold limit values.

Eye/Face Protection:

Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Ensure that an emergency eyewash station and safety shower are located nearby.

Skin Protection:

To prevent repeated or prolonged skin contact, wear oil and solvent resistant impervious clothing, gloves (such as neoprene or nitrile), and boots.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations at a level that is adequate to protect worker health, a NIOSH/MSHA approved respirator must be worn in accordance with the OSHA respirator standard. Appropriate respirators may include air-purifying cartridge respirators for organic vapors, supplied air respirators, or self-contained breathing apparatus (in environments with unknown concentrations or emergency situations).

Other/General Protection:

Wear body-covering clothes to avoid prolonged or repeated exposure. Launder before reuse. Varying application methods can dictate the use of additional protective safety equipment such as impermeable aprons, etc.

Ingredient(s) – Exposure Limits

Petroleum Hydrocarbon Naphtha	
OSHA PEL for Oil Mist:	5 mg/m ³ (8-hour TWA)
OSHA PEL for Stoddard Solvent (CAS 8052-41-3):	2900 mg/m ³ or 500 ppm (8-hour TWA)
ACGIH TLV for Oil Mist	5 mg/m ³ (8-hour TWA)
ACGIH TLV for Stoddard Solvent (CAS 8052-41-3):	100 ppm (8-hour TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White to light colored liquid
Odor:	Hydrocarbon solvent odor
Chemical Type:	Mixture
Physical State:	Liquid
Melting Point:	-46° F
Boiling Point:	367 – 394° F, 186 – 201° C
Specific Gravity:	0.78 – 0.80
Percent Volatiles:	100
Percent VOCs:	100
Packing Density:	6.5 – 6.7 lb./gal.
Vapor Pressure:	<1 mm Hg @ 68° F (0.075, 0.23, 0.50, 0.500 mm Hg @ 68° F as reported)
Vapor Density:	>1 (air = 1)
Solubility:	Negligible
Evaporation Rate:	151 (Ether = 1), 0.04 (n-Bu Acetate = 1)

Physical properties given are typical for this material. Exact data varies depending upon supplier.

CRYSTAL CLEAN 140+

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to Avoid (stability):

Avoid heat and open flames, strong acids, and strong oxidizers.

Incompatible Materials:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition may result in an airborne mixture of solids (smoke and soot), liquids (mist), and gases including a complex mixture of fumes, carbon monoxide, carbon dioxide, aldehydes, and other organic hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Acute Studies:

Stoddard Solvent or Mineral Spirits

Oral (LD ₅₀):	>34,600 mg/kg (rat)
Gas (LC ₅₀):	>21,400 mg/kg for 4 hours (rat)
Dermal (LD ₅₀):	15,400 mg/kg (rabbit)

Eye Effects:

Negligible eye irritation produced in rabbits.

Skin Effects:

Moderate skin irritation produced in rabbits.

Chronic/Carcinogenicity:

Animal data indicate that repeated exposures that cause severe skin irritation may cause or promote skin cancer.

Neurotoxicity:

Repeated exposures that cause acute neurological effects may also cause long-term neurological deficits in humans.

Miscellaneous Toxicological Information:

Reports of animal studies using both sexes of several species have shown that kidney effects can occur in male rats after prolonged and repeated inhalation exposures to light hydrocarbon vapors of the general type that can be represented in this product. While the effects are of a low order of severity in animals, the implications of these results for humans have not yet been determined.

Animal data suggest that slight anemia, adaptive liver changes, and kidney toxicity (male rat nephropathy) may be caused by repeated overexposure to some similar solvents. The significance of this data to humans is unknown. Additional studies show at very high oral doses, similar products caused irreversible damage to the stomach, liver, and kidneys (male only) of rats. These effects are not relevant to humans at occupational levels of exposure.

Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.

Toxicity data provided from tests reported on similar solvent products and conducted by Shell Chemical Company (MSDS #7653, September 20, 2001) and by ExxonMobil Chemical Company (MSDS # 92875673).

CRYSTAL CLEAN 140+

12. ECOLOGICAL INFORMATION

Releases to water and streams may cause fouling of water. May be toxic to aquatic animals.

13. DISPOSAL CONSIDERATIONS

Maximize material recovery for reuse or recycling. It is the responsibility of the user to determine if the material is a RCRA hazardous waste at the time of disposal. Dispose properly in accordance with federal, state, and local regulations.

RCRA Information:

If this material becomes a waste, it should not be hazardous waste characteristic for ignitability (D001) by RCRA criteria (40 CFR 261) unless contaminated by other materials or hazardous wastes.

14. TRANSPORT INFORMATION

Proper Shipping Name: Petroleum Distillates, n.o.s., Combustible Liquid, UN1268, PG III

Hazard Class: Combustible Liquid

DOT Identification Number: UN1268

DOT Shipping Label: Combustible Liquid (United States only)

Packaging Exceptions: 49 CFR 173.150

Packaging Requirements: 49 CFR 173.203, 49 CFR 173.242

US DOT Emergency Response Guidebook Guide No.: 128

This material is not classified as hazardous under IATA and IMDG regulations.

15. REGULATORY INFORMATION

U. S. Regulatory Information:

TSCA: This material is listed in the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory (CASRNs 64742-47-8, 64742-88-7).

CWA: This material is classified as an oil under Section 311 of the Clean Water Act (CWA, 40 CFR 110) and the Oil Pollution Act of 1990. Spills and discharges that cause a sheen on surface waters or in waterways and sewers that lead to surface waters must be reported to the National Response Center at 1-800-424-8802.

CERCLA: The following materials have reportable quantities (RQ) listed under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA or 40 CFR 302.4(a)):

<u>Component</u>	<u>RQ (lbs.)</u>
None	

SARA 302 Components: The following components are listed as Extremely Hazardous Substances under the Emergency Planning and Community Right-To-Know Act (EPCRA or 40 CFR 355, Appendix A):

<u>Component</u>
None

CRYSTAL CLEAN 140+

SARA Hazard Classes:

Acute health hazard
Fire hazard


SARA Section 313 Notification and Components: This product contains the following constituents in concentrations at or above de minimus levels and which are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of the Superfund amendments and Reauthorization Act of 1986 (SARA). The act also requires that this notice accompany the MSDS in all redistributions and may not be detached or omitted from future copies.

Component CASRN:
None

Hazard Ratings:

0 = No hazard
1 = Minimal hazard
2 = Moderate hazard
3 = High hazard
4 = Severe hazard

NFPA



NPCA - HMIS



16. OTHER INFORMATION

Precautionary Label:

WARNING: Combustible Liquid
Contains Petroleum Distillates!
May be harmful or fatal if swallowed!
Keep out of reach of children!

Revision/Preparer Information:

MSDS Preparer: Douglas Lozier
MSDS Preparer Telephone Number 317-875-4670

Reference Documentation:

Information provided in this Material Safety Data Sheet is supplied by Heritage Crystal Clean, L.L.C. with material safety data sheets of same or similar products of Shell Chemical Company, Superior Solvents and Chemical Company, and Ashland Specialty Chemical Company.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Heritage Crystal Clean, L.L.C.



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION: . . : ANTICORIT RF 2675AJ-55GL DR

MANUFACTURER IDENTIFICATION

Company Name : FUCHS LUBRICANTS CO.
Address : 17050 LATHROP AVE.
HARVEY IL 60426
Telephone : 708-333-8900
Emergency Contact : Regulatory Compliance Department
Emergency Telephone . . . : 708-333-8900 (8am - 5pm CST, M-F)
800-255-3924 (24 Hours)

MSDS PRINT DATE : 03/31/2006

* EMERGENCY OVERVIEW

This product is a liquid that is insoluble in water.
Direct eye contact may cause temporary irritation. Short term skin
exposure is not expected to be irritating. Inhalation and ingestion are
not anticipated routes of exposure during normal conditions of use.

* HMIS Rating: Health- 1 Flammability- 1 Reactivity- 0 PPE- X

SECTION 2 - COMPONENT DATA

Components listed in this section may contribute to the potential
hazards associated with exposure to the concentrate. The product may
contain additional non-hazardous or trade-secret components.

Mineral Oil Cas#: proprietary Percent: < 95
Exposure Limit:
ACGIH TLV: 5 mg/m3 (as mist)
ACGIH STEL: 10 mg/m3 (as mist)
OSHA PEL: 5 mg/m3 (as mist)

- Carcinogenic Components: This product contains no carcinogens.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS and SYMPTOMS from SHORT TERM/ACUTE EXPOSURE:

- EYE EXPOSURE -
This product is not expected to cause eye irritation under normal
conditions of use. Symptoms of temporary eye irritation and redness
may result upon direct contact or when exposed to high mist levels in
poorly ventilated areas.
- SKIN EXPOSURE -
Short term skin contact is not expected to cause skin irritation.
Prolonged or repeated direct exposure to the skin may result in

FUCHS LUBRICANTS CO.



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

symptoms of irritation and redness. In severe cases, prolonged or repeated contact may result in dermatitis accompanied by symptoms of irritation, itching, dryness, cracking and/or inflammation.

- INHALATION -

This product has low volatility and so is not expected to cause respiratory tract irritation during normal conditions of use. Exposure to high mist levels in poorly ventilated areas may cause upper respiratory tract irritation and difficulty breathing.

- INGESTION -

Ingestion may cause slight stomach irritation and discomfort.

POTENTIAL CHRONIC HEALTH EFFECTS:

No further data known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

No further data known.

CARCINOGENICITY:

This product is not listed as a known or suspected carcinogen by IARC, OSHA, or the NTP.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Upon direct eye contact, hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. If irritation is due to exposure to mist or vapors, remove the individual to fresh air. If irritation persists, flush the eyes with clean water until the irritation subsides. If symptoms persist, contact a physician.

SKIN CONTACT:

Remove product from the skin by washing with a mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact a physician.

INHALATION:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs, remove the employee to fresh air. Contact a physician or other medical professional if irritation or distress persists.

INGESTION:

If small amounts are ingested, first aid measures are not likely to be necessary. If larger amounts are ingested or if symptoms of ingestion occur, dilute stomach contents with two glasses of water or milk. (NOTE: Do NOT give anything by mouth to an unconscious person.) Do not induce



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

vomiting without medical supervision. If vomiting occurs spontaneously keep airway clear. If symptoms of ingestion persist, seek medical attention.

NOTE TO PHYSICIAN:
No further data known.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES:

Flashpoint : 285.0 °F COC
Flammability Limits : LEL -N/A
UEL -N/A

EXTINGUISHING MEDIA:

In accordance with NFPA guidance, dry chemical, foam, or CO2 fire extinguishers are all acceptable. Note that while water fog extinguishers are also acceptable, do NOT apply a direct stream of water onto burning product because it may cause spreading and increase fire intensity.

UNUSUAL FIRE & EXPLOSION HAZARDS:

None known.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Emergency responders in the danger area should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See Section 8 of the MSDS for other PPE to be worn as conditions warrant.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP MEASURES:

Important: As with any spill or leak, before responding ensure that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn. See Section 8 of this MSDS for PPE recommendations.

If possible, safely contain the spill with dikes or other spill response equipment appropriate for petroleum or organic material releases. Take measures to prevent spreading of product. Note that while product will ignite it will not readily burn. However, as a precaution eliminate ignition sources. Prevent from entering sewers or waterways. Large volumes may be transferred to an appropriate container for proper disposal. Small volumes or residues may be soaked up with absorbents. Spill response materials should be collected for proper disposal.

SECTION 7 - HANDLING AND STORAGE

HANDLING:



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty drums and containers. Keep containers closed when not in use.

Product residue in empty containers is combustible but will not readily burn. NOTE however, that excessive heating or cutting of empty containers may create an ignition source sufficient to start a fire and in extreme cases, cause an explosion.

STORAGE:

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

SPECIAL COMMENTS:

No further data known.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

- EYE PROTECTION -

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full face shield is recommended.

- SKIN PROTECTION -

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistant gloves such as butyl or nitrile are recommended.

Where splashing or soaking is likely, wear oil or chemical resistant clothing to prevent exposure.

- RESPIRATORY PROTECTION -

A respirator may be worn to reduce exposure to vapors, dust, or mist. Select a NIOSH/MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in 29 CFR 1910.134.

ENGINEERING CONTROLS:

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lowest practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000(d)(2) and the ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance : Clear amber
Odor : Petroleum
Physical State : Liquid
Water Solubility : Insoluble
Specific Gravity : .886

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES:

This product is incompatible with strong oxidizing agents.

DECOMPOSITION PRODUCTS MAY INCLUDE:

Thermal decomposition products are dependent on combustion conditions. A complex mixture of airborne solid, liquid, particulates and gasses may evolve when the material burns. Combustion byproducts may include:
oxides of carbon,
oxides of sulfur,
incompletely burned hydrocarbons as fumes and smoke.

CONDITIONS TO AVOID:

Avoid contact with incompatible materials and exposure to extreme temperatures.

POLYMERIZATION:

This product is not expected to polymerize.



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

STABILITY:

This product is stable.

SECTION 11 - TOXICOLOGICAL INFORMATION

EYE EFFECTS:

No further toxicological data known.

SKIN EFFECTS:

No further toxicological data known.

ORAL EFFECTS:

No further toxicological data known.

INHALATION EFFECTS:

No further toxicological data known.

OTHER:

No further data known.

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

ENVIRONMENTAL FATE:

The degree of biodegradability and persistence of this product has not been determined.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Ensure that collection, transport, treatment, and disposal of waste product, containers and rinsate complies with all applicable laws and regulations. Note that use, mixture, processing, or contamination of the product may cause the material to be classified as a hazardous waste. It is the responsibility of the product user or owner to determine at the time of disposal, whether the product is regulated as a hazardous waste.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARDOUS MATERIAL INFORMATION:

* Not otherwise DOT regulated.

SECTION 15 - REGULATORY INFORMATION

FUCHS LUBRICANTS CO.



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

FEDERAL REGULATIONS:

SARA 313:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Clean Water Act / Oil Pollution Act:

This product contains mineral oil and is subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

CERCLA Reportable Quantity:

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

Component	RQ
* - * - * - * - * - * - * - * - * - * - * - * - *	

Toxic Substances Control Act:

The components of this product are listed on the TSCA Inventory.

Ozone Depleting Substances:

This product contains no ozone depleting substances as defined by the Clean Air Act.

Hazardous Air Pollutants:

Any components listed below are defined by the Federal EPA as hazardous air pollutants.

Component
* - * - * - * - * - * - * - * - * - * - * - * - *

STATE REGULATIONS:

This product contains mineral oil, and as used, may be regulated by state used oil regulations. Check with the appropriate state agency to determine whether such a regulation exists.

No further data known.

SECTION 16 - OTHER INFORMATION

Prepared by : Corporate Regulatory Compliance
Date of issue : 03/31/2006
Last Revision Date : 02/11/2006
2707412

FUCHS LUBRICANTS CO.



PRODUCT NAME: ANTICORIT RF 2675AJ-55GL DR

NOTICE: This MSDS provides a good faith representation of information believed to be accurate as of the last revision date. This document does not create any express or implied product warranties. Since conditions of use are beyond the control of Fuchs Lubricants Co., all risks associated with product use are assumed by the user.
